US ERA ARCHIVE DOCUMENT

CATALOG DOCUMENTATION
NATIONAL COASTAL ASSESSMENT DATABASE
NORTHEAST REGION 2000-2002
WATER QUALITY MEASUREMENTS: PHYSICAL AND NUTRIENT DATA

TABLE OF CONTENTS

- 1. DATASET IDENTIFICATION
- INVESTIGATOR INFORMATION
- 3. DATASET ABSTRACT
- 4. OBJECTIVES AND INTRODUCTION
- 5. DATA ACQUISITION AND PROCESSING METHODS
- 6. DATA MANIPULATIONS
- 7. DATA DESCRIPTION
- 8. GEOGRAPHIC AND SPATIAL INFORMATION
- 9. QUALITY CONTROL AND QUALITY ASSURANCE
- 10. DATA ACCESS AND DISTRIBUTION
- 11. REFERENCES
- 12. TABLE OF ACRONYMS
- 13. PERSONNEL INFORMATION
- 1. DATASET IDENTIFICATION
 - 1.1 Title of Catalog document
 National Coastal Assessment Database
 Northeast Region 2000-2002

Water Quality Measurements: Physical and Nutrient Data

- 1.2 Authors of the Catalog entry John Kiddon, U.S. EPA NHEERL-AED Harry Buffum, Raytheon
- 1.3 Catalog revision date August 2007
- 1.4 Dataset name
 Water Quality Measurements
- 1.5 Task Group
 National Coastal Assessment-Northeast
- 1.6 Dataset identification code
 003
- 1.7 Version 001
- 1.8 Request for Acknowledgment

EMAP requests that all individuals who download EMAP data acknowledge the source of these data in any reports, papers, or presentations. If you publish these data, please include a statement similar to: "Some or all of the data described in this article were produced by the U. S. Environmental Protection Agency through its Environmental Monitoring and Assessment Program (EMAP)".

- 2. INVESTIGATOR INFORMATION
- 2.1 Principal Investigators
 Donald Cobb, U.S. EPA NHEERL-AED
 Walter Galloway, U.S. EPA NHEERL-AED
 Stephen Hale, U.S. EPA NHEERL-AED
 John Kiddon, U.S. EPA NHEERL-AED

Norman Rubinstein, U.S. EPA NHEERL-AED Charles Strobel, U.S. EPA NHEERL-AED Henry Walker, U.S. EPA NHEERL-AED

- 2.2 Sample Collection Investigators Donald Cobb, U.S. EPA NHEERL-AED
- 2.3 Sample Processing Investigators John Kiddon, U.S. EPA NHEERL-AED

3. DATASET ABSTRACT

3.1 Abstract of the Dataset

The Water Quality Measurements data file reports physical water quality parameters measured in the field and concentrations of nutrients measured from samples collected for the National Coastal Assessment during the summers of 2000-02. Included is information regarding dissolved oxygen, pH, conductivity, salinity, temperature, transparency (secchi depth), ammonium, nitrate and nitrite, nitrite, orthophosphate, chlorophyll a, and total suspended solids. Physical parameters were generally measured in the surface and bottom layers of the water column, while nutrients were generally reported for three water layers, surface, mid-depth, and bottom, except for shallow stations (< 2m). At shallow stations, measurements were performed at only one intermediate water depth and values reported identically in both surface-layer and bottom-layer parameters. One record is presented for each analyte measured per level per sampling event.

3.2 Keywords for the Dataset
Temperature, dissolved oxygen, pH, depth, conductivity, salinity,
secchi depth, ammonium, nitrate, nitrite, orthophosphate, total suspended
solids, chlorophyll a

4. OBJECTIVES AND INTRODUCTION

4.1 Program Objective

The National Coastal Assessment (NCA) is a national monitoring and assessment program with the primary goal of providing a consistent evaluation of the estuarine condition in U.S. estuaries. It is an initiative of the Environmental Monitoring and Assessment Program (EMAP), and is a partnership of several federal and state environmental agencies, including: EPA's Regions, Office of Research and Development, and Office of Water; state environmental protection agencies in the 24 marine coastal states and Puerto Rico; and the United States Geological Survey (USGS) and the National Oceanic and Atmospheric Agency (NOAA). The five-year NCA program was initiated in 2000, and is also known as the Coastal 2000 Program.

Stations were randomly selected using EMAP's probabilistic sampling framework and were sampled once during a summer index period (June to October). A consistent suite of indicators was used to measure conditions in the water, sediment, and in benthic and fish communities. The measured data may be used by the states to meet their reporting requirements under the Clean Water Act, Section 305(b). The data will also be used to generate a series of national reports characterizing the condition of the Nation's estuaries.

4.2 Dataset Objective

The objective of the Water Quality Measurements data file is to characterize physical and nutrient water quality parameters, measured during 2000-02 in surface, mid-depth and bottom water layers of Northeastern U.S. estuaries.

4.3 Dataset Background Discussion

A two-year sampling design was employed for $2000-2001\ \mathrm{NCA}$ program in the Northeast. Analysts may therefore wish to consider the two years of data together.

This database contains data collected in 2000-02 from the Northeast component of the NCA, measured in the estuaries of the states Maine through Delaware. Nine federal-state cooperative agreements were formed to conduct the NCA program in Northeast U.S. Samples were analyzed either by a national lab under contract to the EPA or by in-state labs.

The physical water quality parameters contained in this file include dissolved oxygen, pH, conductivity, salinity, temperature and Secchi depth. A continuous profile of these parameters (except Secchi depth) is measured with a CTD lowered and raised through the water column. Surface, mid-depth and bottom measurements are reported in this summary database. At some shallow stations, measurements were performed only at one intermediate water depth and values reported identically in both surface-layer and bottom-layer parameters. If the Secchi disc hit the bottom, the reading may have been inaccurate (the true Secchi depth may have been deeper). These conditions are flagged with a Quality Assurance code.

Some of the measured nutrient values are smaller than the Method Detection Limit (MDL). Such 'non-detects' are reported as zero, and the record is associated with a QA Code. The user may wish to substitute values other than zero for the result, e.g., set the non-detect value to the MDL value, half the MDL value, etc.

Massachusetts did not participate in the NCA program in 2002. Rhode Island conducted fish trawls only in 2002, and collected physical water parameters in conjunction with the trawls. Connecticut collected all parameters, but at an abbreviated group of in-shore stations (stations in the Long Island Sound intended for sampling in 2002 were sampled in 2003).

4.4 Summary of Dataset Parameters

Surface, mid-depth and bottom physical and nutrient water quality parameters plus secchi depth are recorded to reflect estuarine conditions in the Northeast United States.

5. DATA ACQUISITION AND PROCESSING METHODS

5.1 Data Acquisition

The sample collection methods used by USEPA trained field crews will be described here. Any significant variations by NCA partners are noted in Section 5.1.12.

5.1.1 Sampling Objective

Obtain in situ measurements of temperature, salinity, conductivity, dissolved oxygen, pH and secchi depth in the surface and bottom layers.

Seawater was collected and filtered for use in the measurement of nutrient, phytoplankton and total suspended solids concentrations. Samples were collected in the surface, mid, and bottom water layers, except at some shallow stations (water depth < 2m) where a single mid-depth sample was taken.

5.1.2 Sample Collection: Methods Summary

Temperature, salinity, conductivity, dissolved oxygen, and pH were measured with a Hydrolab Datasonde or similar instrument, and water clarity was measured using a Secchi disk. The Hydrolab was lowered through the water column, and parameter values were recorded every meter for the first five meters and every two meters thereafter, including a value one meter above

the bottom. Only the parameter values measured one meter below the surface and one meter above the bottom are reported in this data file. At some shallow stations (water depth less than 2 m), measurements were performed at only one intermediate water depth and the values reported identically in both surface-layer and bottom-layer parameters.

A seawater sample was collected from surface, mid-depth, and bottom water layers with a 5L Go-Flo sampling bottle for nutrient analysis. At some shallow locations (water depth < 2m) only one mid-depth water sample was taken. Duplicate water samples from the same cast were filtered aboard ship with 0.7-micron glass-fiber filter pads (not all duplicates were analyzed), and both the filtered water and filter were immediately frozen. Replicate field samples were also taken from separate casts at approximately 10% of the stations to evaluate the repeatability of the sampling procedure.

5.1.3 Beginning Sampling Dates

7 July 2000

25 June 2001

25 June 2002

5.1.4 Ending Sampling Dates

20 October 2000

31 October 2001

31 October 2002

5.1.5 Sampling Platform

Samples were collected from gasoline or diesel powered boats, 18 to 133 feet in length

5.1.6 Sampling Equipment

Hydrolab DataSonde 3 multi-probe data logging units were used. The software program Procomm was used to set up and download profile logging runs to a laptop computer. A YSI dissolved oxygen meter (Model M58) was used to check the Hydrolab DO and temperature readings. Hand-held refractometers were used to QC the Hydrolab salinity measurements. A 20 cm diameter Secchi disk was used with a line marked in 0.2 m intervals. A 5 L Go-Flo sampling bottle was employed to collect water samples for nutrient analysis.

5.1.7 Manufacturer of Sampling Equipment Data logger: Hydrolab Corp., Austin, TX. Dissolved Oxygen probe: YSI Inc.

5.1.8 Key Variables Not applicable

5.1.9 Sample Collection: Calibration

Calibration of the Hydrolab dissolved oxygen sensor was performed using the air calibration method as described by the manufacturer. The pH probe was calibrated using pH 7 and 10 standard buffer solutions. The salinity sensor was calibrated against a standard whose salinity was measured by a laboratory salinometer (Guildline AutoSal Model 8400) calibrated with IAPSO Standard Seawater ("Copenhagen water"). The salinity measurements were also checked in the field against a hand-held refractometer as a rough check. The YSI dissolved oxygen meters were calibrated immediately prior to each station using the water-saturated air calibration procedure recommended by the manufacturer. The refractometers were calibrated using deionized water and a higher salinity standard traceable to "Copenhagen water".

5.1.10 Sample Collection: Quality Control Surface values of temperature, salinity and dissolved oxygen measured by the Hydrolab were routinely compared with independent measurements performed on a bucket of surface water. The Hydrolab values were considered acceptable if the following criteria were met: the two temperature values agree to within two degrees Celsius, salinity values agree to within three ppt, and dissolved oxygen values agree to within 0.5 mg/L. The Secchi depth values were measured by different crew members until values agreed within 0.1 meter.

Duplicate field samples for nutrients from independent casts were taken, representing about 10% of all events. All nutrients were measured on these duplicates. Precision estimates are reported in 7.1.2.

5.1.11 Sample Collection: References Strobel, C.J. 2000. Coastal 2000-Northeast Component: Field Operations Manual U. S. Environmental Protection Agency, National Health and Environmental Effects Research Laboratory, Atlantic Ecology Division, Narragansett, RI. EPA/620/R-00/002.

U.S. EPA. 2001. National Coastal Assessment: Field Operations Manual. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/003. 72 p.

5.1.12 Sample Collection: Alternate Methods

The different partners used the following equipment:

Partner Water Profile Equipment

CT Sea-bird SBE-19 CT-FSH Sea-bird SBE-19

DE Hydrolab Datasonde

MA Hydrolab Datasonde; Quanta

MA-FSH Hydrolab Datasonde
ME Hydrolab Datasonde
NH YSI model 6600_M
NJ-C Hydrolab Datasonde
NJ-DB Hydrolab Datasonde

NY YSI model 6600_M; YSI 85; Seabird model 25

RI Hydrolab Datasonde RI-FSH Hydrolab Datasonde

Connecticut, Long Island Sound and Connecticut, LIS Fish Survey did not perform pH or Secchi depth measurements.

5.2 Data Preparation and Sample Processing
No analytical processing was involved for the physical data.

The processing procedures of the core NCA nutrient parameters described here are the methods of the national contract laboratory. Any significant variations in procedures used by other state labs are noted in Section 5.1.12.

5.2.1 Sample Processing Objective

Water samples were analyzed to measure the concentrations of water column nutrients, total suspended solids and phytoplankton pigments.

5.2.2 Sample Processing: Methods Summary
Filters and filtrate were delivered frozen from sampling locations
following a filtration operation using a 0.7 micron glass-fiber filter
(see Section 5.1.2). NH4, PO4, NO23, and NO2 were measured by
analyzing filtered water with a segmented continuous flow analyzer.

Chlorophyll a pigments were extracted from filter with 90% acetone and measured without acidification, using the Weshmeyer method. TSS was measured by drying the filter at 103 to 105 °C followed by weighing.

- 5.2.3 Sample Processing: Calibration Standard laboratory procedures were followed to assure analytical instruments were calibrated.
- 5.2.4 Sample Processing: Quality Control
 Approximately 5% of all filtered water samples were reanalyzed by the analytical laboratory to determine analytical repeatability of the analytical procedure. Another 5% of dissolved water samples were spiked with a known quantity of constituent and reanalyzed as a test for recovery efficience. For particulate constituents, 10% of all samples were reanalyzed (particulate samples cannot be spiked). Processing quality was considered acceptable if duplicate analyses were consistent within 10% and spiked analyses were as expected within 15%.
- 5.2.5 Sample Processing: References D'Elia, C.F., Connor, E.E., Kaumeyer, N.L., Keefe, C.W., Wood, K.V., and Zimmermann, C.F. (1997). Nutrient Analytical Services Laboratory Standard Operating Procedures. Technical Report Series 158-97. Chesapeake Biological Laboratory, University of Maryland Center for Environmental Science, Solomons, MD: 77 pp.
- U.S. EPA. 2001. Environmental Monitoring and Assessment Program (EMAP): National Coastal Assessment Quality Assurance Project Plan 2001-2004. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/002. 189 p.

Welschmeyer, N.A. 1994. Fluorometer analysis of chlorophyll a in the presence of chlorophyll b and pheopigments. Limnology and Oceanography 39:1985-1992.

- 5.2.6 Sample Processing: Alternate Methods Not Applicable
- 6. DATA ANALYSIS AND MANIPULATIONS 6.1 Name of New or Modified Value Surface and bottom measurements
- 6.2 Data Manipulation Description
 Surface and bottom measurements were extracted from continuous water
 profile data files by (1) sorting all records from the same water profile
 by depth; (2) selecting the first (minimum depth) record for all surface
 values; (3) selecting the last (maximum depth) for all bottom measures.

Nutrient concentrations smaller than the method detection limit were reported as zero.

7. DATA DESCRIPTION

7.1 Description of Parameters

7.1.1 Components of the Dataset

Attribute Name	Format	Description
Data Group Code Sampling Year Station Name Sampling Collection Date Latitude Decimal Degrees		Data Group Conducting Sampling Year When Data Were Collected The Station Identifier Date of Sample Collection Decimal degrees of latitude
Longitude Decimal Degrees Water Column Sampled	NUMBER(9.3)	Decimal degrees (-) of longitude Location of collection (i.e., surface, bottom)
Water Measurement Name Water Measurement Value Measurement Units Measurement Depth Depth Units Type Measurement Method Used	NUMBER(13.6) VARCHAR2(15) NUMBER(5.1) VARCHAR2(15) VARCHAR2(40)	Name of measurement Measurement or concentration Units of measure Measurement Depth Units of measure Vertical profile or ambient Analysis or collection method

7.1.2 Precision of Reported Values

The values are accurate to no more than three significant digits; however more significant digits may be reported in the dataset because of formatting restrictions.

PARAMETER	PRECISION	MIN	MAX	UNITS
Secchi depth	0.1	0.1	9.5	meter
Temperature (surface)	0.01	10.9	30.2	deg C
Salinity (surface)	0.01	0.0	34.8	ppt
Dissolved oxygen (surface)	0.01	0.4	16.4	mg/L
pH (surface)	0.01	3.11	9.36	pH unit
Temperature (bottom)	0.01	5.61	30.2	deg C
Salinity (bottom)	0.01	0.0	34.8	ppt
Dissolved oxygen (bottom)	0.01	0.42	15.6	mg/L
pH (bottom)	0.01	3.14	9.34	pH unit
Depth	0.1	0.1	44.5	meter
Dissolved Ammonia as N	0.001	0.001	2.28	mg/L
Diss Nitrite and Nitrate as 1	N 0.0001	0.0002	4.61	mg/L
Dissolved Nitrite as N	0.0001	0.0001	0.13	mg/L
Dissolved Phosphate as P	0.001	0.001	0.493	mg/L
Chlorophyll a	0.01	0.09	95.0	ug/L
Total Suspended Solids	0.1	0.72	272	mg/L

7.1.3 Minimum Value in Dataset See Section 7.1.2

7.1.4 Maximum Value in Dataset See Section 7.1.2

7.2 Data Record Example

7.2.1 Column Names for Example Records

Data Group, Sampling Year, Station Name, Sampling Collection Date, Latitude Decimal Degrees, Longitude Decimal Degrees, Water Column Sampled, Water Measurement Name, Water Measurement Value, Measurement Units, Measurement Depth, Depth Units, Type Measurement, Method Used, QA Code

7.2.2 Example Data Records

National Coastal Assessment-Northeast/Connecticut,2000,CT00-0001-A, 17-AUG-2000,41.151,-73.22,Bottom,Dissolved oxygen,4.77,mg/L,1.6,m, Vertical profile,CTD,,

National Coastal Assessment-Northeast/Connecticut,2000,CT00-0001-A, 17-AUG-2000,41.151,-73.22,Bottom,Salinity,25.56,ppt,1.6,m, Vertical profile,CTD,,

National Coastal Assessment-Northeast/Connecticut,2000,CT00-0001-A, 17-AUG-2000,41.151,-73.22,Mid-depth,Phosphorus,0.9,mg/L,1.6,m,ambient,Go-Flo bottle,,

8. GEOGRAPHIC AND SPATIAL INFORMATION

- 8.1 Minimum Longitude (Westernmost) -75.6977 decimal degrees
- 8.2 Maximum Longitude (Easternmost) -67.0482 decimal degrees
- 8.3 Minimum Latitude (Southernmost) 38.4739 decimal degrees
- 8.4 Maximum Latitude (Northernmost) 45.1848 decimal degrees
- 8.5 Name of area or region

The National Coastal Assessment Northeast Region covers the northeastern US coastline from Maine to Delaware.

- 9. OUALITY CONTROL AND OUALITY ASSURANCE
- 9.1 Measurement Quality Objectives

The measurement quality objectives of the EMAP-Estuaries program specify accuracy and precision requirements of 10% in the water physical parameters. Reference: U.S. EPA. 2001. Environmental Monitoring and Assessment Program (EMAP): National Coastal Assessment Quality Assurance Project Plan 2001-2004. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/002. 189 p.

9.2 Data Quality Assurance Procedures

The physical data were reviewed to assure consistency among partners regarding sampling procedures, reporting format, etc. All measurements were performed in the field.

QA procedures for nutrients included running blanks, spiked samples, and standard reference materials with each batch of samples. Any batch failing to meet the specifications presented in Section 9.1 was reanalyzed or rejected.

9.3 Actual Measurement Quality

No field replicates were measured for the physical parameters. All of the nutrient data reported met the QA specifications listed in Section 9.1.

- 10. DATA ACCESS
- 10.1 Data Access Procedures

Data can be downloaded from the web at: http://www.epa.gov/emap/nca/html/data/

10.2 Data Access Restrictions None

10.3 Data Access Contact Persons
John Kiddon, U.S. EPA NHEERL-AED, Narragansett, RI
401-782-3034, 401-782-3030 (FAX), kiddon.john@epa.gov

Harry Buffum, Data Manager, Raytheon, Narragansett, RI 401-782-3183, 401-782-3030 (FAX), buffum.harry@epa.gov

- 10.4 Dataset Format
 Tab-delimited ASCII files
- 10.5 Information Concerning Anonymous FTP
 Not available
- 10.6 Information Concerning WWW See Section 10.1 for WWW access
- 10.7 EMAP CD-ROM Containing the Dataset Data not available on CD-ROM

11. REFERENCES

Strobel, C.J. 2000. Environmental Monitoring and Assessment Program: Coastal 2000 - Northeast component: field operations manual. Narragansett (RI): U.S. Environmental Protection Agency, National Health and Environmental Effects Research Laboratory, Atlantic Ecology Division. EPA/620/R-00/002. 68 p.

- U.S. EPA. 2001. National Coastal Assessment: Field Operations Manual. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/003. 72 p.
- U.S. EPA. 2001. Environmental Monitoring and Assessment Program (EMAP): National Coastal Assessment Quality Assurance Project Plan 2001-2004. U.S. Environmental Protection Agency, Office of Research and Development, National Health and Environmental Effects Research Laboratory, Gulf Ecology Division, Gulf Breeze, FL. EPA/620/R-01/002. 189 p.

12. TABLE OF ACRONYMS

AED Atlantic Ecology Division

deg C degrees Centigrade

EMAP Environmental Monitoring and Assessment Program

EPA Environmental Protection Agency

mg/L Milligrams per Liter

NCA National Coastal Assessment

NHEERL National Health and Environmental Effects Research Laboratory

ppt parts per thousand

QA/QC Quality Assurance/Quality Control

WWW World Wide Web

13. PERSONNEL INFORMATION

Sandra Benyi, Research Biologist U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3041, 401-782-3030 (FAX), benyi.sandra@epa.gov

Harry Buffum, Database Manager, Raytheon U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3183, 401-782-3030 (FAX), buffum.harry@epa.gov Don Cobb, Chemist U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-9616, 401-782-3030 (FAX), cobb.donald@epa.gov

Walter Galloway, NCA Project Officer
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3096, 401-782-3030 (FAX), galloway.walt@epa.gov

Steve Hale, EMAP Information Manager U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3048, 401-782-3030 (FAX), hale.stephen@epa.gov

Melissa Hughes, Data Librarian, Raytheon U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3184, 401-782-3030 (FAX), hughes.melissa@epa.gov

John Kiddon, AED Oceanographer U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3044, 401-782-3030 (FAX), kiddon.john@epa.gov

Joe LiVolsi, AED QA Officer
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3163, 401-782-3030 (FAX), livolsi.joseph@epa.gov

Norman Rubinstein, NCA Project Officer U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3015, 401-782-3030 (FAX), pesch.gerald@epa.gov

Charlie Strobel, AED Analyst U.S. Environmental Protection Agency, NHEERL-AED 27 Tarzwell Drive, Narragansett, RI 02882-1197 401-782-3180, 401-782-3030 (FAX), strobel.charles@epa.gov

Hal Walker, AED Analyst
U.S. Environmental Protection Agency, NHEERL-AED
27 Tarzwell Drive, Narragansett, RI 02882-1197
401-782-3134, 401-782-3030 (FAX), walker.henry@epa.gov